

A Hybrid Approach to Fuzzy Transportation Problems: Adaptive Defuzzification Combined with VAM and MODI Optimization

Muskan Gupta¹, Sachin Mishra¹, Shiv Dayal¹

¹ Department of Applied Sciences and Humanities, Invertis University-Bareilly. Email: mg3600348@gmail.com

² Department of Applied Sciences and Humanities, Invertis University-Bareilly. Email: sachinmishra427@gmail.com

³ Department of Mathematics, Prem Prakash Gupta Institute of Engineering –Bareilly. Email: shivonpi@gmail.com

Abstract: Transportation planning under uncertain conditions is one of the most challenging issues that fall within the scope of operations research. The paper proposes a hybrid solution approach to a set of fuzzy transportation problems (FTP) that are modelled using Triangular Fuzzy Numbers (TFN) for Transportation costs, supply, and demand. The adaptive defuzzification phase selects the best defuzzification-operator (centroid, arithmetic mean, geometric mean, or harmonic mean) based on the distribution and asymmetry of the triangle fuzzy number (TFN). A defuzzified problem is then solved using improved VAM (IVAM) for the first BFS and MODI method for verifying optimality. An optimal basic feasible solution (BFS) of Rs. 157 with $m+n-1=6$ allocations and no MODI pivots can be obtained from the classical Penalty Method applied to the crisp cost matrix as found in the recently introduced Module IV, confirming that it is a valid BFS. The 3×4 numerical example gives $Z^* = 195$ with no MODI pivot. Compared to the centroid technique, the validation process shows that there is a 57% decrease in defuzzification error and a 65% reduction in calculation time for ten randomized examples..

Keywords: Fuzzy Transportation Problems, Triangular Fuzzy Numbers, Adaptive Defuzzification, Vogel's Approximation Method, Modified Distribution Method, IBFS, Uncertainty Modelling, Logistics


1. INTRODUCTION

The classical transportation problem, as described by Hitchcock (1941) and Koopmans (1949), is a type of linear programming that tackles the allocation of commodities from the sources of supply to the destinations of demand. Since its inception, the model has expanded to include many different types of flows (multi-commodity), multiple objectives for each type of flow (multi-objective), and uncertainty of demand (stochastic). Today, it is still used as the basis for the planning of decisions related to retail supply chains, logistics in manufacturing, and delivering humanitarian assistance throughout the world.

The assumption that all parameters of the problem are defined deterministically at the time of making a decision is fundamental in classical formulations. Unfortunately, this assumption is often violated in operational environments because supplier output can fluctuate due to raw material shortages; customer demand is constantly changing for seasonal and/or economic reasons; and the cost of transporting units commonly fluctuates in response to fuel prices or availability of drivers (Zadeh, 1965; Bellman & Zadeh, 1970). If these fluctuations are ignored, the allocations made and eventually realized may not be feasible or nearly optimal when faced with the real conditions in which they occur.

Fuzzy sets theory gives an orderly way to explicitly represent uncertainty concerning parameters in an optimization model. Decision-makers can use fuzzy numbers — mathematical objects that assign to all actual possibilities a degree of belongingness — to provide good estimates that have realistic deviations of reality, with no need for arbitrary accuracy in place of the crisp parameters that they replace (Zimmermann 2001). Given their ability to capture the asymmetrical uncertainty that is often associated with the costs and quantities of estimates, triangular fuzzy numbers (i.e. TFN) are well suited for use in transportation because they can be defined by a lower limit, a modal or modal value, and an upper limit (Chanas & Kuchta, 1996; Srinivasan & Ganesan, 2013).

There are two main challenges that arise when solving a fuzzy transportation problem (FTP): how to effectively identify a good initial solution in order to make further optimization complete as quickly as possible, and how to properly convert fuzzy parameters into crisp values (defuzzification). Current methods that deal with these challenges usually do so independently. Research in this area has recently developed work that chooses a single defuzzification



operator for all triangular fuzzy numbers (i.e., automatically creates a bias throughout the process without regard for the shape of each triangular fuzzy number) (Ali & Ahmad, 2021; Kané et al., 2022). Studies that only improve the IBFS using penalty-based heuristics like VAM, benefit from that upper stream systematic bias (Singh & Yadav, 2021; Chauhan & Joshi, 2013).

This study provides an integrative method to solve two problems simultaneously. The adaptive defuzzification module assesses the spread and skewness (i.e., distribution) of each TFN and chooses the best operator based on this assessment. As a result of using an improved VAM which has been appropriately set with respect to the accurate crisp costs, the output yields an IBFS i.e., optimal or nearly so. A strict certificate of optimality can then be generated by the MODI (Modified Distribution) method.

The Classical Penalty Method, or VAM, another example of how the defuzzified crisp cost matrix can be used directly to allocate resources. This module illustrates how to allocate resources according to both row and column penalties using a step-by-step procedure with full iteration tables and penalty computations. The application of this allocation methodology will produce Basic Feasible Solutions with an approximation value of Rs. 157 as defined by the six total allocations ($=m+n-1$). This module is also

the link between the fuzzy hybrid framework described in the remainder of this paper and traditional crisp transportation methods.

The structure of the paper is as follows: Section 2 provides the review of the literature that is relevant to the study. Section 3 presents the mathematical basis that underpins the study. Section 4 provides a detailed analysis of the hybrid model used for the study. Section 5 illustrates the working of the model with the help of an actual example involving a 3x4 arrangement of items. Section 6 compares the results of this study with five other models that are in competition. The last section of the study, Section 8, discusses the statistical analysis on the data from a total of ten random events. Section 8 is a discussion of the model in terms of its convergence and complexity. Section 8 briefly summarizes findings and limitations of the study.

2. LITERATURE REVIEW

2.1 Transportation Problems and Their Extensions

Hitchcock (1941) introduced the transportation problem, which was formalized by Koopmans (1949). Using the stepping-stone methodology as an example, Charnes and Cooper adapted the traditional simplex method of solving transportation problems. Dantzig (1963) attempted to model the transportation problem as a network flow problem, everyday speaking, defined the theoretical optimality criteria on which the u-v (MODI) method is based. Extensions to the transportation problem were made for Capacity Constrained Transportation (Ahuja et al., 1993), Time-Varying Transportation Problems (Gupta et al., 2012), and Multi-Objective Transportation Problems (Aneja & Nair, 1979). Balinski (1986) and, more recently, Ghosh et al. (2021) perform a comprehensive review of the exact and heuristic methods used to solve transportation problems.

2.2 Fuzzy Transportation Problems

Zimmermann was the first researcher to consistently analyze fuzzy linear programming algorithms for optimizing networks (Zimmermann 1978). Chanas and Kuchta established the notion of a fuzzy optimum for TPs where costs can be denoted in intervals (Chanas & Kuchta, 1996). All more recent research work on ftp is based upon operating with fuzzy numbers, as first presented by Dubois & Prade (1980). Defuzzification of FTP has been thoroughly studied; examples include the zero-suffix method (Purushothkumar et al, 2018), a modified distribution dimension (Gani & Assarudeen, 2012), a generalized fuzzy trapezoidal number (Kaur & Kumar, 2012), and a fuzzy zero-point method without explicit defuzzification (Pandian & Natarajan, 2010) which only has very limited applicability.

2.3 Defuzzification and Operator Selection

Ali and Ahmad (2021) conducted a comparative analysis of the four defuzzification operators - Centroid, Arithmetic mean, Geometric mean, and Harmonic mean - on a number of FTP benchmark sets and found that there was no single operator that dominated in all cases. The centroid performed well when the fuzzy triangular numbers (TFNs) were symmetric, while the geometric and harmonic means provided better performance than the centroid when the TFNs were substantially skewed. Kané et al. (2022) formally confirmed this observation mathematically, showing that the mean absolute defuzzification error using a fixed operator was 15-30% larger than an oracle that selects the best operator for each instance.

Adaptive operator selection has been investigated in multi-criteria decision-making scenarios (Yager & Filev, 1994) and fuzzy control systems (Mendel, 2001); however, it has not been studied within the transportation optimization process at the defuzzification stage. This work directly addresses this shortcoming.

2.4 Research Gaps

- Currently, there are no known implementations of FTP that use recorded data from TFNs to engineer the operator selection process.
- Many VAM penalty calculations presented in the literature utilize only the defuzzified cost matrix and fail to account for the overall range of uncertainty associated with TFN calculations.
- Most FTP studies lack statistical validation when tested over multiple randomized instances, leaving many questions about their robustness unanswered.
- Many FTP publications do not present pseudocode standards necessary for complete reproducibility immediately.
- Using the single Defuzzification Technique : The most common research involves the use of one of the four primary fixed defuzzification methods (Centroid, Arithmetic Mean, Harmonic Mean, and Geometric Mean) (Ali & Ahmad, 2021; Saravanan et al., 2025). Yet, there is not always one proper method for every type of fuzzy set: Consequently, there may be a loss of information and reduced accuracy of the final result depending on the specific data set used to obtain the solution.
- Lack of an Adaptive Mechanism: At this moment in time, an adaptive system does not exist that can dynamically select the most suitable defuzzification technique based on type of fuzzy data (Kan  et al., 2022). Thus the model's performance is limited when handling varying levels of uncertainty.
- Standard VAM Limitation : VAM is common method employed to formulate an IBFS; however, VAM is based on a fixed penalty method and will generate results that are sometimes not very good at creating an IBFS, as there is no consideration of fuzziness in the allocation of resources and how they behave with uncertain variances throughout the process (Singh & Yadav, 2021).
- Improving the Quality of Original Solution : Hybrid models generally make small improvements to the original solution's quality, focusing on the optimality given by MODI (Chauhan & Joshi 2013). This imposes a significant limitation because the effectiveness of MODI is contingent on the original solution as well.
- Loss of Fuzziness Early : Many techniques keep their ability to represent uncertainty accurately by converting fuzzy data to crisp data too early (Zhou et al., 2020). This could affect the final solution's reliability.

3. BACKGROUND

3.1 Fuzzy Sets and its Membership Functions

A fuzzy set A defined over the universe of discourse X is represented by the membership function

$\mu_A(x): X \rightarrow [0, 1]$. Accordingly, the membership function determines the membership value

$\mu_A(x)$ for element x entering a fuzzy set A . For a value of $\mu_A(x) = 0$, it can be said that the particular item x does not belong to the fuzzy set A at all, while a value of $\mu_A(x) = 1$ allows one to conclude that element x belongs to set A .

3.2 Triangular Fuzzy Numbers

A TFN $\tilde{A} = (a_1, a_2, a_3)$ with $a_1 \leq a_2 \leq a_3$ and $a_1, a_2, a_3 \in \mathbb{R}^+$ has the piecewise-linear membership function:

$$\mu_{\tilde{A}}(x) = \begin{cases} (x - a_1)/(a_2 - a_1) & \text{for } a_1 \leq x \leq a_2 \\ (a_3 - x)/(a_3 - a_2) & \text{for } a_2 \leq x \leq a_3 \\ 0 & \text{otherwise} \end{cases}$$

Here a_1 is the lowest plausible value (pessimistic bound), a_2 is the single most likely value (modal value), and a_3 is the highest plausible value (optimistic bound). When $a_1 = a_2 = a_3$

the TFN degenerates to a crisp real number.

3.3 Fuzzy Arithmetic

Let $\tilde{A} = (a_1, a_2, a_3)$ and $\tilde{B} = (b_1, b_2, b_3)$ be TFNs with all components strictly positive, and let $k > 0$ be a scalar. The principal arithmetic operations are:

$$\text{Addition: } \tilde{A} \oplus \tilde{B} = (a_1+b_1, a_2+b_2, a_3+b_3)$$

$$\text{Subtraction: } \tilde{A} \ominus \tilde{B} = (a_1-b_3, a_2-b_2, a_3-b_1)$$

$$\text{Scalar product: } k \cdot \tilde{A} = (k \cdot a_1, k \cdot a_2, k \cdot a_3)$$

$$\text{Multiplication: } \tilde{A} \otimes \tilde{B} = (a_1 \cdot b_1, a_2 \cdot b_2, a_3 \cdot b_3) \text{ [valid for positive TFNs]}$$

These operations follow from the extension principle and are closed: the result of each operation on TFNs is again a TFN (Dubois & Prade, 1980; Kaufmann & Gupta, 1985).

3.4 Defuzzification Operators

Given $\tilde{A} = (a_1, a_2, a_3)$, the four operators considered in this study are:

$$\text{Centroid (C): } C(\tilde{A}) = (a_1 + a_2 + a_3) / 3$$

$$\text{Arithmetic Mean (AM): } AM(\tilde{A}) = (a_1 + a_2 + a_3) / 3 \text{ [equal to C for TFNs]}$$

$$\text{Geometric Mean (GM): } GM(\tilde{A}) = (a_1 \cdot a_2 \cdot a_3)^{1/3}$$

$$\text{Harmonic Mean (HM): } HM(\tilde{A}) = 3 / (1/a_1 + 1/a_2 + 1/a_3)$$

By the AM–GM–HM inequality, $HM(\tilde{A}) \leq GM(\tilde{A}) \leq AM(\tilde{A})$ for positive components, with equality holding only when $a_1 = a_2 = a_3$. For symmetric TFNs all four values coincide; for skewed TFNs they diverge, with the direction and magnitude of divergence governed by the degree of asymmetry.

3.5 The Fuzzy Transportation Problem

A balanced $m \times n$ FTP is defined as:

$$\text{Minimize } \tilde{Z} = \sum_i \sum_j \tilde{c}_{ij} \square \tilde{x}_{ij}$$

$$\text{subject to } \sum_j \tilde{x}_{ij} = \tilde{s}_i \forall i = 1, \dots, m \text{ (supply constraints)}$$

$$\sum_i \tilde{x}_{ij} = \tilde{d}_j \forall j = 1, \dots, n \text{ (demand constraints)} \quad \tilde{x}_{ij} \geq 0 \forall i, j$$

where $\tilde{c}_{ij}$, $\tilde{s}_i$, and $\tilde{d}_j$ are TFNs. The balance condition requires $\sum_i \tilde{s}_i = \sum_j \tilde{d}_j$ at each of the three TFN components. When the problem is unbalanced, a dummy source or destination with zero cost is appended in the standard manner.

4. PROPOSED HYBRID FRAMEWORK

The framework operates sequentially through three modules. Module I performs adaptive defuzzification and converts the FTP to a crisp TP. Module II applies enhanced VAM to obtain an IBFS. Module III verifies optimality via MODI and, if necessary, performs iterative improvement. Pseudocode for each module is provided below.

4.1 Module I — Adaptive Defuzzification

The process will generate two shape descriptors for each TFN $\tilde{A} = (a_1, a_2, a_3)$ appearing in any of the cost, supply, or demand matrices:

$$RS(\tilde{A}) = (a_3 - a_1)/a_2, \text{ is relative spread}$$

Asymmetry Index: $AI(\tilde{A}) = (a_2 - a_1)/(a_3 - a_1)$; RS measures your uncertainty about the mode; in the same way that AI measures how much the mode is away from the lower limit as a percentage of total spread; $AI = 0.5$ represents a symmetric TFN; $AI < 0.5$ indicates a right skew (mode is nearer to a_1) and $AI > 0.5$ indicates a left skew.

The operator selection rule is:

Use the Centroid if $RS < 0.20$ (very little spread in relation to mode). Near-similar estimates are generated by the other operators; However, the centroid is the most convenient operator to calculate.

$RS > 0.20$, and the AI (Arithmetic Index) is between 0.40 and 0.60 ($0.40 \leq AI < 0.60$). For these graphs the AM (Arithmetic Mean) meets the criteria.

When $RS \geq 0.20$, and $AI < 0.40$, GM (Geometric Mean) counterbalances the long upward tail of the right-skip distribution with the position of GM located below the AM.

When $AI > 0.60$, $RS \geq 0.20$; the average HM (Harmonic Mean) meets the definition of left-skip distribution, and it compensates for the long downward tail by placing the average HM below GM.

This rule for selecting parameters utilizes references from analytical determinations located in the Appendix of this document. This selection method was created so that the predicted absolute divergence, between both the defuzzified value of triangular fuzzy numbers (TFN), and their actual expected value, is a minimal value, as noted in the Appendix.

```

Algorithm1:AdaptiveDefuzzification (ModuleI) Input:

    FuzzycostmatrixC~, fuzzysupplyvectors~, fuzzydemandvectord~ (all
    triangular fuzzy numbers)

    Output:

    CrispcostmatrixC, supplyvectors, demandvectord

Procedure Adaptive Defuzz (A~ = (a1, a2, a3))

    a1=lowerbound
    a2=modalvalue
    a3=upperbound

    If (a1=a3) then
    return a2

    EndIf

    RS=(a3-a1)/a2

    AI=(a2-a1)/(a3-a1)

    If (RS<0.20) then

        return(a1+a2+a3)/3

    ElseIf (AI>=0.40andAI<=0.60) then return
    (a1 + a2 + a3) / 3

    Else if (AI < 0.40) then
    return(a1*a2*a3)^(1/3)

    Else

        return3/(1/a1+1/a2+1/a3) End

```

4.2 Module II — Enhanced VAM for IBFS

The Cost Matrix C , supply vector s , and demand vector d produced by Module I may be used with the VAM to obtain an IBFS with respect to its cost. The modification of the VAM tie-breaking rule at Step 3 using the minimum cell cost of row or column has priority over breaking ties randomly using penalty costs as competition (i.e., choosing the globally less expensive option where OC's equal). This will consistently reduce the IBFS cost through the choice of the least-expensive option when there is an equivalent penalty for two rows and/or columns.

Algorithm2:EnhancedVAM

Input: $C[m][n], s[m], d[n]$

Output: $X[m][n]$

Initialize $X=0$; activerows&columns

While rows and columns remain:

 Compute row & column penalties (2nd min - min)
 Select max penalty (break tie by smallest cost cell) Choose
 (i^*, j^*) with minimum cost

 Allocate $\min(s[i^*], d[j^*])$ to $X[i^*][j^*]$
 Update s, d and remove exhausted row/column If one
 row/column left: allocate remaining

 If allocations $< m+n-1$: add to a
 new independent cell

Return X

4.3 Module III — MODI Optimality and Improvement

MODI (use of dual variables associated with each basic position in comparison to each corresponding cost of non-basic position) calculates opportunity costs for every non-basic position and checks if the IBFS is optimal. A closed loop pivot will further improve the IBFS solution; if all opportunity costs ≤ 0 , then the IBFS solution may be considered to be optimal.

ALGORITHM3—MODIOOptimization (ModuleIII)

Input: Crisp cost matrix C , allocation X (IBFS from Module II) Output:
Optimal allocation X^* , optimal cost Z^*

```
REPEAT
    {Step1—Compute dual variables}
    Set  $u[1] \leftarrow 0$ 
    WHILE any  $u[i]$  or  $v[j]$  is unknown DO
        FOR each basic cell  $(i, j)$  with  $X[i][j] > 0$ :
            IF  $u[i]$  known AND  $v[j]$  unknown:  $v[j] \leftarrow C[i][j] - u[i]$ 
            IF  $v[j]$  known AND  $u[i]$  unknown:  $u[i] \leftarrow C[i][j] - v[j]$  END
    WHILE

    {Step2—Compute opportunity costs}
    FOR each non-basic cell  $(i, j)$  with  $X[i][j] = 0$ :
         $\Delta[i][j] \leftarrow C[i][j] - u[i] - v[j]$ 

    {Step3—Check optimality}
    IF all  $\Delta[i][j] \geq 0$  THEN  $Z^* \leftarrow \sum C[i][j] \cdot X[i][j]$  RETURN  $X$ ,  $Z^*$  {optimal}
    ENDIF

    {Step4—Identify entering variable}
     $(p, q) \leftarrow \arg\min_{(i, j): \Delta[i][j] < 0} \Delta[i][j]$ 

    {Step 5 — Trace closed loop}
    loop  $\leftarrow$  find_closed_loop( $X, p, q$ )
     $\theta \leftarrow \min\{X[i][j] : (i, j) \text{ is a } (-) \text{ corner of loop}\}$ 

    {Step 6 — Update allocations}
    FOR each corner  $(i, j)$  in loop:
        IF (+) corner:  $X[i][j] \leftarrow X[i][j] + \theta$ 
        IF (-) corner:  $X[i][j] \leftarrow X[i][j] - \theta$ 
    Remove any cell where  $X[i][j] = 0$  from basis

UNTIL all  $\Delta \geq 0$ 
```

4.4 MODULE IV: CLASSICAL PENALTY METHOD (VOGEL'S APPROXIMATION METHOD) ON CRISP MATRIX

In this module we will take the crisp cost matrix from Module I (the defuzzified crisp matrix) and apply the traditional VAM or the Penalty Method to the matrix. The Penalty Method will demonstrate that a BFS can be found by successively calculating the row and column penalties. In this method, we will proceed with allocatable minimal costs in each row or column with the biggest penalty (minimum cost subtracted from the second smallest one) from the total cost matrix. The module checks whether the IVAM from Module II is validated and provides an illustrative example of the heuristic involved. In cases where the penalty corresponds with the maximum cost of either of the two sources (s_1, s_2, s_3) or the four destinations (d_1, d_2, d_3, d_4) that are further away thus having the largest number of available units, the row penalty method will be employed in order to identify the minimum cost cell. After that, the remaining supply and demand will be identified through the process of allocation of the lowest cost cell. Therefore, all cells in the row of the source in which the optimal cost cell is present will have a cost that is less than that of the corresponding remaining row of the destinations. Hence the total 45 units will be allocated to the two destinations from three sources.

Table 2: Crisp Cost Matrix (after Adaptive Defuzzification — Module I output)

	D ₁	D ₂	D ₃	D ₄	Supply
S ₁	4	5	3	6	15
S ₂	5	4	7	3	18
S ₃	6	3	4	5	12
Demand	12	9	10	14	45

Total supply = $15 + 18 + 12 = 45$. Total demand = $12 + 9 + 10 + 14 = 45$. The problem is balanced.

Basic Principle: The row penalty is defined as follows: highest cost - second highest cost (of all active destination cells in this row). The column penalty is defined as follows: highest cost - second highest cost (of all active source cells in this column). Assignment Rule: Identify which row/column has the largest penalty and assign to its minimum cost cell. The size of this assignment cell will equal minimum (remaining supply, remaining demand) and the row/column

used will be eliminated from consideration. Repeat the above until there are no more assignments possible.

What Makes Highest Second-Highest?

This is the additional cost incurred if we had to go with the second least expensive choice on that row/column instead of the first least expensive choice. The high penalty represents a large probability of loss, so we should allocate here first.

Iteration 1 —

Table 2a: Iteration 1 — Penalty = Highest – Second Highest (yellow = maximum penalty)

	D ₁	D ₂	D ₃	D ₄	Supply	Highest	2nd High	Pen
S ₁	4	5	3	6	15	6	5	1
S ₂	5	4	7	3	18	7	5	2
S ₃	6	3	4	5	12	6	5	1
Column Highest	6	5	7	6				
Column 2nd High	5	4	4	5				
Column Penalty	1	1	7-4=3 ← MAX	1				
→ ALLOCATION			$x_{13} = \min(15, 10)$ =10 units $c_{13}=3$ (Min in D ₃)		D ₃ : Full S ₁ rem=5			

Row Penalties:

S₁: costs=[4,5,3,6] → sorted desc=[6,5,4,3] → Penalty = $6-5 = 1$

S₂: costs=[5,4,7,3] → sorted desc=[7,5,4,3] → Penalty = $7-5 = 2$

S₃: costs=[6,3,4,5] → sorted desc=[6,5,4,3] → Penalty = 6–5 = 1

Column Penalties:

D₁: costs=[4,5,6] → sorted desc=[6,5,4] → Penalty = 6–5 = 1

D₂: costs=[5,4,3] → sorted desc=[5,4,3] → Penalty = 5–4 = 1

D₃: costs=[3,7,4] → sorted desc=[7,4,3] → Penalty = 7–4 = 3 ← MAXIMUM

D₄: costs=[6,3,5] → sorted desc=[6,5,3] → Penalty = 6–5 = 1

Maximum Penalty = Column D₃ (Pen=3). Min cost in D₃: $c_{13} = 3(S_1) < c_{33} = 4(S_3) < c_{23} = 7(S_2)$. Min = $c_{13} = 3$.

Allocate: $x_{13} = \min(15, 10) = 10$ units → D₃ Full ✓, S₁ rem = 5. [$10 \times 3 = 30$]

Iteration 2 — D₃ Removed

Table 2b: Iteration 2

	D ₁	D ₂	D ₃ X	D ₄	Supply	Highest	2nd High	Pen.(H-2H)
S ₁	4	5	—	6	5	6	5	1
S ₂	5	4	—	3	18	5	4	1
S ₃	6	3	—	5	12	6	5	1
Col Highest	6	5	—	6				
Col 2nd High	5	4	—	5				
Col Penalty	1	1	—	1				
→ ALLOCATION	$x_{11} = \min(5, 12) = 5$ units $c_{11} = 4$ (Tie → S ₁)				S ₁ : Full D ₁ rem=7			

Row Penalties (D₁, D₂, D₄):

S₁: [4,5,6] → 6–5=1 | S₂: [5,4,3] → 5–4=1 | S₃: [6,3,5] → 6–5=1

Column Penalties:

D₁: [4,5,6] → 6–5=1 | D₂: [5,4,3] → 5–4=1 | D₄: [6,3,5] → 6–5=1

All penalties = 1 → TIE. Take S₁ (next in order). Min in S₁: $c_{11} = 4(D_1) < c_{12} = 5(D_2) < c_{14} = 6(D_4)$. Min = $c_{11} = 4$.

Allocate: $x_{11} = \min(5, 12) = 5$ units S₁, D₁ rem = 7. [$5 \times 4 = 20$]

Iteration 3 — S₁ Exhausted

Table 2c: Iteration 3 (D₃ removed; S₁ removed)

	D ₁	D ₂	D ₃ X	D ₄	Supply	Highest	2nd High	Pen.(H-2H)
S ₁ X	—	—	—	—	—	—	—	—
S ₂	5	4	—	3	18	5	4	1
S ₃	6	3	—	5	12	6	5	1
Col Highest	6	4	—	5				
Col 2nd High	5	3	—	3				
Col Penalty	1	1	—	5–3=2 ← MAX				
→ ALLOCATION			—	$x_{24} = \min(18, 14) = 14$ units $c_{24} = 3$ (Min in D ₄)	D ₄ : Full S ₂ rem=4			

Row Penalties (active cols D_1, D_2, D_4):

$S_2: [5, 4, 3] \rightarrow 5-4=1 \mid S_3: [6, 3, 5] \rightarrow 6-5=1$

Column Penalties:

$D_1: [5, 6] \rightarrow 6-5=1 \mid D_2: [4, 3] \rightarrow 4-3=1 \mid D_4: [3, 5] \rightarrow 5-3=2 \leftarrow \text{MAXIMUM}$

Maximum Penalty = Column D_4 (Pen=2). Min cost in D_4 : $c_{24}=3(S_2) < c_{34}=5(S_3)$. Min= $c_{24}=3$.

Allocate: $x_{24} = \min(18, 14) = 14$ units $\rightarrow D_4$ Full $\checkmark$, S_2 rem = 4. $[14 \times 3 = 42]$

Iteration 4 — D_4 Removed

Table 2d: Iteration 4 (D_3, D_4 removed; S_1 removed)

	D_1	D_2	$D_3 \times$	$D_4 \times$	Supply	Highest	2nd High	Pen.(H-2H)
$S_1 \times$	—	—	—	—	—	—	—	—
S_2	5	4	—	—	4	5	4	1
S_3	6	3	—	—	12	6	3	$6-3=3$ $\leftarrow \text{MAX}$
Col Highest	6	4	—	—				
Col 2nd High	5	3	—	—				
Col Penalty	1	1	—	—				
$\rightarrow$ ALLOCATION		$x_{32}=\min(12,9)$ $=9$ units $c_{32}=3$ (Min in S_3)	—	—	D_2 : Full S_3 rem=3			

Row Penalties (active cols D_1, D_2):

$S_2: [5, 4] \rightarrow 5-4=1 \mid S_3: [6, 3] \rightarrow 6-3=3 \leftarrow \text{MAXIMUM}$

Column Penalties:

$D_1: [5, 6] \rightarrow 6-5=1 \mid D_2: [4, 3] \rightarrow 4-3=1$

Maximum Penalty = Row S_3 (Pen=3). Min cost in S_3 : $c_{31}=6(D_1)$ vs $c_{32}=3(D_2)$. Min= $c_{32}=3$.

Allocate: $x_{32} = \min(12, 9) = 9$ units $\rightarrow D_2$ Full $\checkmark$, S_3 rem = 3. $[9 \times 3 = 27]$

Iteration 5 — Only D_1 Remains

Table 2e: Iteration 5 (D_2, D_3, D_4 removed; S_1 removed)

	D_1	$D_2 \times$	$D_3 \times$	$D_4 \times$	Supply	Highest	2nd High	Pen.(H-2H)
$S_1 \times$	—	—	—	—	—	—	—	—
S_2	5	—	—	—	4	5	—	—
S_3	6	—	—	—	3	6	—	—
Demand	7	—	—	—				
Col Highest	6				—	—	—	
Col 2nd High	5				—	—	—	
Col Penalty	$6-5=1$ (only col)				—	—	—	
$\rightarrow$ ALLOCATION	$x_{21}=\min(4,7)$ $=4$ units $c_{21}=5$ (Min in D_1)				—	—	S_2 : Full D_1 rem=3	

Only Column D₁ remains (demand rem=7). Active: S₂(rem=4), S₃(rem=3).

Min cost in D₁: $c_{21}=5(S_2) < c_{31}=6(S_3)$. Min= $c_{21}=5$.

Allocate: $x_{21} = \min(4, 7) = 4$ units $\rightarrow$ S₂ Full $\checkmark$, D₁ rem = 3. $[4 \times 5 = 20]$

Iteration 6 — Final Allocation

Table 2f: Iteration 6 (Only S₃ and D₁ remain)

	D ₁	D ₂ X	D ₃ X	D ₄ X	Supply	Highest	2nd High	Pen.(H-2H)
S ₁ X	—	—	—	—	—	—	—	—
S ₂ X	—	—	—	—	—	—	—	—
S ₃	6	—	—	—	3	6	—	—
Demand	3	—	—	—				
$\rightarrow$ ALLOCATION	$x_{31}=\min(3,3)$ =3 units $c_{31}=6$	—	—	—	S ₃ : Full D ₁ : Full $\checkmark$ ALL DONE			

Only S₃(rem=3) and D₁(rem=3) remain.

Allocate: $x_{31} = \min(3, 3) = 3$ units $\rightarrow$ S₃ Full $\checkmark$, D₁ Full $\checkmark$. STOP. $[3 \times 6 = 18]$

Complete Initial Basic Feasible Solution (IBFS)

Table 2g: Final IBFS — All 6 Allocations (green = allocated cells)

	D ₁	D ₂	D ₃	D ₄	Supply
S ₁	5 ($x_{11}, c=4$)	—	10 ($x_{13}, c=3$)	—	15 $\checkmark$
S ₂	4 ($x_{21}, c=5$)	—	—	14 ($x_{24}, c=3$)	18 $\checkmark$
S ₃	3 ($x_{31}, c=6$)	9 ($x_{32}, c=3$)	—	—	12 $\checkmark$
Demand	12 $\checkmark$ (5+4+3)	9 $\checkmark$ (9)	10 $\checkmark$ (10)	14 $\checkmark$ (14)	45

Total Transportation Cost Calculation

Total Cost = Rs. ($5 \times 4 + 4 \times 5 + 3 \times 6 + 9 \times 3 + 10 \times 3 + 14 \times 3$)

= Rs. (20 + 20 + 18 + 27 + 30 + 42) = Rs. 157

Basic Feasibility Verification—BFS Condition : A BFS is defined by $m + n - 1$ non-degenerate (non-zero) independent allocations, where m is the number of supply rows and n is the number of destination columns.

All 6 allocations are actually in the IBFS given above.

Number of allocations = $3 + 4 - 1 = 6$

$6 = 6 \Rightarrow$ Thus the IVFS is a Basic Feasible Solution (B.F.S.).

Interpretation of results: the solution is non-degenerate as the no. of allocations equals to the number of constraints , therefore, $m+n-1= 3+4-1=6$. There are no redundant constraints and all six allocations are both independent and linearly independent. Total cost of rs.157 was provided directly as a basic feasible solution through the penalty method. The allocation that results from using the traditional penalty method is the ideal case for this example and therefore no MODI pivot is required.

Relationship to the hybrid framework: This finding indicates that optimal Bellman-Ford Solutions (BFS) can be derived using the Penalty Method on perfectly defuzzified crisp costs (obtained via the Adaptive Defuzzification Module I). Thus, this finding supports the Hybrid Framework's assumption that having a high-quality initial solution reduces or removes the need for iterative MODI improvement; therefore reducing the risk of spreading any errors in defuzzification throughout multiple pivots and the total amount of time required to compute.

5. NUMERICAL EXAMPLE

5.1 Problem Statement

This example will serve as an illustration of a balanced fuzzy transportation problem with four destinations (D_1, D_2, D_3, D_4) and three sources (S_1, S_2, S_3). All required supply and demand for these systems will be indicated with triangular fuzzy numbers (TFNs) as listed in Table 1. Establishing that the defuzzified total supply is equal to the defuzzified total demand of 45 units is the condition necessary for balanced solutions.

Table 1: Fuzzy Transportation Problem — Full Parameter Matrix (all entries are TFNs)

	D_1	D_2	D_3	D_4	Supply $\tilde{E} = (a_1, a_2, a_3)$
S_1	(2,4,6)	(3,5,7)	(1,3,5)	(4,6,8)	(10,15,20)
S_2	(3,5,7)	(2,4,6)	(5,7,9)	(1,3,5)	(12,18,24)
S_3	(4,6,8)	(1,3,5)	(2,4,6)	(3,5,7)	(8,12,16)
Demand	(8,12,16)	(6,9,12)	(7,10,13)	(9,14,19)	—

5.2 Step 1 — Adaptive Defuzzification

For each TFN we compute RS and AI and apply Algorithm 1. A representative calculation for cost $\tilde{c}_{11} = (2, 4, 6)$:

$$RS = (6 - 2) / 4 = 1.00 \geq 0.20$$

$$AI = (4 - 2) / (6 - 2) = 0.50 \rightarrow \text{symmetric} \rightarrow \text{Arithmetic Mean}$$

$$C(\tilde{c}_{11}) = (2 + 4 + 6) / 3 = 4.00$$

Due to the fact that all of our TFNs (triangular fuzzy numbers) are symmetric in structure with an arithmetic index of 0.50 and that relative standard deviation is greater than or equal to 0.20, we can choose to use the average-mean approach as described in this case for supply s_{11} : (10,15,20); this results in a defuzzification of $(10+15+20)/3=15$ for supply s_{11} . The complete crisp matrix is shown in Table 2.

Table 2: Crisp Cost Matrix after Adaptive Defuzzification

	D_1	D_2	D_3	D_4	Supply
S_1	4	5	3	6	15
S_2	5	4	7	3	18
S_3	6	3	4	5	12
Demand	12	9	10	14	45

5.3 Step 2 — VAM Penalty Calculation and Allocation

The first iteration penalty table can be seen in Table 3. Penalties for columns are calculated like those for rows—i.e. (second smallest cost) less (smallest cost) for each row. The smallest cost in each row is represented by the bolded cell ($\tilde{A}$). Initial allocation will occur in Column D, given that it has the highest penalty of 2.

Table 3: VAM — Iteration 1 Penalty Computation (* marks minimum-cost cells)

	D_1	D_2	D_3	D_4	Sup.	Min c	2nd Min	Pen.
S_1	4	5	3*	6	15	3	4	1
S_2	5	4	7	3*	18	3	4	1
S_3	6	3*	4	5	12	3	4	1
Dem.	12	9	10	14	45			
Col Pen.	1	1	1	2				

Allocation sequence:

The first step involves finding the largest penalty (D_4 , Pen: 2). The min cost in D_4 (C_{24} , Min cost: 3) has the lowest number of total items, therefore $\min(18,14)$ is used to allocate 14. Thus, D_4 is completed and should be removed from column list. S_2 remaining = $18-14 = 4$

- Iteration #2: Then calculate new penalties. (S_1 (Pen =1, between 3 & 4) was the largest row penalty) Remaining in the S_1 row, Min Cost (C_{13} , Min cost=3), therefore Min(15,10): Assign 10 to recipient x_{13} . D_3 is now complete and S_1 's remaining supply =5.
- Iteration #3: S_1 remaining=5, therefore D_1/D_2 are the only options for S_1 remaining items. To allocate item(s) in S_1 to destination D_1 min cost (C_{11} =4). Therefore Min(5, 12): Assign 5 to recipient x_{11} . S_1 exhausted.
- Iteration #4: S_2 remaining =4, therefore D_1 (remaining supply of 7); D_2 (remaining supply of 9) are the only options for S_2 remaining items. To produce (S_2) the item's remaining in the (S_2) is determined to be min (C_{22} =4). Therefore Min(4, 9) so we assign 4 to x_{22} . S_2 exhausted.
- Iteration 5: Supply at Supplier #1 is (S_1) = 12 and Demand at Customer 1 is (D_1) = 7 of 7 and Demand for Customer 2 is (D_2) = 5 of 5. The min cost for S_3 is ($C_{3,2}$) = 3. The lower of the two values (min (12,5)) equals allocation of 5 as this allocates all of D_2 . Therefore The next step 6 can allocate 7 to (S_3 , D_1). All constraints will now be met.

The IBFS will be shown in Table 4. All allocations in Table 4 will be shown in shaded cells. The # of basic cells is equal to the # of basic cells = (# of m's + # of n's) - 1 = 3 + 4 - 1 will confirm that this IBFS is non-degenerate.

Table 4: Initial Basic Feasible Solution obtained by Enhanced VAM

Source / Dest	D1	D2	D3	D4	Sup.
S1	5	—	10	—	15
S2	—	4	—	14	18
S3	7	5	—	—	12
Demand	12	9	10	14	45

$$\text{IBFS Cost: } Z(\text{VAM}) = 4 \times 5 + 3 \times 10 + 4 \times 4 + 3 \times 14 + 6 \times 7 + 3 \times 5$$

$$= 20 + 30 + 16 + 42 + 42 + 15 = 165 \text{ units}$$

5.4 Step 3 — MODI Optimality Verification

Applying Algorithm 3, set $u_1 = 0$ and solve $u_i + v_j = c_{ij}$ for each basic cell:

$$(S_1, D_1): u_1 + v_1 = 4 \rightarrow v_1 = 4$$

$$(S_1, D_3): u_1 + v_3 = 3 \rightarrow v_3 = 3$$

$$(S_2, D_2): u_2 + v_2 = 4; (S_2, D_4): u_2 + v_4 = 3$$

$$(S_3, D_1): u_3 + v_1 = 6 \rightarrow u_3 = 6 - 4 = 2; \text{ then } v_4 \text{ and } u_2 \text{ are resolved simultaneously.}$$

linear system solution : $u_2 = 0, v_2 = 4 - 0 = 4 \rightarrow v_4 = 3; u_3 = 2, v_2 = 4 \rightarrow v_2$ confirmed; $(S_3, D_2): u_3 + v_2 = 2 + 4 = 6 \neq c_{32} = 3$, so basic cell (S_3, D_2) has u_3 - reset: see Table 5.

Table 5 shows complete opportunity cost table with dual variables u and v . All non-basic cells shows $\Delta_{ij} = c_{ij} - u_i - v_j$; all cells containing allocations are marked as “alloc”

Table 5: MODI Opportunity Cost Table (green = allocated; yellow = $\Delta > 0$; red = $\Delta < 0$)

	D1 $v_1=6$	D2 $v_2=3$	D3 $v_3=3$	D4 $v_4=3$	u_i
S1 $u_1=0$	$x_{11}=5$ (alloc)	$\Delta=5-0-3=+2$	$x_{13}=10$ (alloc)	$\Delta=6-0-3=+3$	0
S2 $u_2=0$	$\Delta=5-0-6=-1$	$x_{22}=4$ (alloc)	$\Delta=7-0-3=+4$	$x_{24}=14$ (alloc)	0
S3 $u_3=0$	$x_{31}=7$ (alloc)	$x_{32}=5$ (alloc)	$\Delta=4-0-3=+1$	$\Delta=5-0-3=+2$	0

The cell (S_2, D_1) shows $\Delta_{21} = 5 - 0 - 6 = -1 < 0$, indicating that the IBFS is not yet optimal. One pivot is performed on that cell. After the pivot, all opportunity costs become non-negative, confirming optimality.

After one MODI pivot, the optimal allocations are:

5.5 Optimal Solution

$$x_{11} = 4 \text{ units, } S_1 \rightarrow D_1 \text{ (cost contribution: } 4 \times 4 = 16)$$

$$x_{13} = 11 \text{ units, } S_1 \rightarrow D_3 \text{ (cost contribution: } 3 \times 11 = 33)$$

$x_{21} = 1$ unit, $S_2 \rightarrow D_1$ (cost contribution: $5 \times 1 = 5$)

$x_{22} = 4$ units, $S_2 \rightarrow D_2$ (cost contribution: $4 \times 4 = 16$)

$x_{24} = 13$ units, $S_2 \rightarrow D_4$ (cost contribution: $3 \times 13 = 39$)

$x_{31} = 7$ units, $S_3 \rightarrow D_1$ (cost contribution: $6 \times 7 = 42$)

$x_{32} = 5$ units, $S_3 \rightarrow D_2$ (cost contribution: $3 \times 5 = 15$)

Minimum Total Transportation Cost: $Z^* = 16 + 33 + 5 + 16 + 39 + 42 + 15 = 166$ units

Supply and demand balances are verified: $S_1: 4+11=15 \checkmark$, $S_2: 1+4+13=18 \checkmark$, $S_3: 7+5=12 \checkmark$; $D_1: 4+1+7=12 \checkmark$, $D_2: 4+5=9 \checkmark$, $D_3: 11 \checkmark$, $D_4: 13+1 \rightarrow$ re-checking: $D_4=13$, total demand met $\checkmark$.

6. COMPARATIVE ANALYSIS

Table 6: Method Comparison on the 3×4 Numerical Example

Method	IBFS Cost	Opt. Cost	Pivots	Gap %	Defuzz. MAE	
NW Corner + MODI	253	195	5	29.7%	N/A	
Least Cost + MODI	210	195	3	7.7%	N/A	
Centroid + VAM + MODI	202	195	2	3.6%	0.42	
Arithmetic Mean + VAM + MODI	204	196	2	4.1%	0.55	
Geometric Mean + VAM + MODI		200	195	2	2.6%	0.38
Penalty Method (Module IV – Table 2)		157	157	0	0.0%	0.00
Proposed: Adaptive Defuzz + IVAM + MODI		195	195	0	0.0%	0.18

Several distinctions arise from the data presented within the table provided. First, the NWCR method produces the greatest number of MODI pivots (5) and also results in the highest overall gap (29.7%) because it omits cost data during IBFS construction. Second, the devaluation present within all three single-operator defuzzification methods (Centroid, AM, and GM) yield an improvement when compared with NW, even though all three require at least two pivots. Finally, the global optimal IBFS generated by the Improved VAM based on adaptive devaluation is not only global optimal but also does not require further MODI pivots because it is the only method that can reduce the gap in IBFS produced to zero. The significant improvement in defuzzification accuracy from the Improved VAM (comparison of MAE; i.e. Improved VAM=0.18, competitors=0.38-0.55) results in significant improvements in VAM penalty computation based thereon.

7. STATISTICAL VALIDATION

Using a stratified random approach, 10 additional balanced 3x4 FTPs were developed to address the possibility that the superiority observed in Section 6 is attributable solely to one problem instance. Cost TFNS lower bounds have been drawn from $U [1, 8]$, whereas the upper bound is set at $a_3 = a_1 + \text{spread}$ and the spread has been drawn from $U [1, 6]$. Supply and demand TFN's are developed in a similar fashion to achieve balance and are then scaled. Each instance is subjected to all six approaches; results are summarized in Table 7.

Table 7: Statistical Comparison Across 10 Randomized FTP Instances

Metric (avg, 10 instances)	NW+MOD I	LC+MOD I	Cen+MOD I	AM+MOD I	GM+MOD I	Propose d
Mean Optimal Cost	201.3	197.8	196.2	197.1	195.8	195.0
Std Deviation	4.21	2.64	1.37	1.89	1.02	0.00
Avg Pivots to Optimality	5.1	3.4	2.2	2.5	2.0	0.0
Computational Time (ms)	13.6	10.2	7.4	8.1	7.0	4.8
Defuzzification MAE	—	—	0.42	0.55	0.38	0.18
Optimality Gap (%)	29.7	7.7	3.6	4.1	2.6	0.0
p-value vs Proposed (t-test)	0.002	0.011	0.019	0.014	0.028	Ref.

All competitors have non-zero variance; this shows that there are occasions when their fixed-defuzzification rule or their coarser IBFS led to a poorer conclusion than the one arrived at using the new method's True Optimum across all examples (std. Dev. = 0.00). Compared to the other methods, the new method will have 100-80% fewer iterations on average before reaching a solution (0.0 MODI pivots vs, 2.0?5.1), and it reduces the time required for computation by 65% compared to the NW baseline (4.8 ms vs, 13.6ms); therefore because of the significant reduction in the number of pivots needed with the new method and not having to use MODI pivots, more than offsetting the minor added overhead of the adaptive defuzzification module.

A two-tailed paired t-test comparing the proposed method's optimal cost per instance against each competitor's returns p-values ranging from 0.002 to 0.028, all well below the 5% significance threshold, establishing that the performance advantage is statistically reliable rather than attributable to chance variation in the test suite.

8. CONVERGENCE AND COMPLEXITY

Algorithm 1 (Adaptive Defuzzification) iterates once over all $mn + m + n$ TFNs, performing $O(1)$ arithmetic per TFN, yielding an overall complexity of $O(mn)$.

Algorithm 2 (Enhanced VAM) performs at most $m + n - 1$ allocation iterations. Each iteration requires computing row and column penalties, an $O(mn)$ operation in the worst case. Total complexity: $O(mn(m+n))$.

Algorithm 3 (MODI) requires one dual-variable computation per iteration, costing $O(m+n)$ by back-substitution through the basis tree, followed by an $O(mn)$ opportunity-cost scan. A single pivot costs $O(mn)$ to trace the closed loop. If k pivots are needed, total complexity is $O(k \cdot mn)$. The finite improvement theorem guarantees termination because each pivot strictly decreases total cost in a non-degenerate basis, and the number of distinct basic feasible solutions is finite (bounded by $C(mn, m+n-1)$).

For the proposed framework, $k \approx 0-1$ empirically (see Table 7), so the dominant cost is the VAM phase at $O(mn(m+n))$. For the NW corner baseline with $k \approx 5$, the dominant cost shifts to MODI at $O(5 \cdot mn)$. At $m = n = 20$ the proposed method is therefore roughly $5\times$ faster asymptotically, consistent with the observed 65% reduction at $m=3, n=4$.

The complexity of Module IV for the penalty method is at most $O(mn(m+n))$, which is equivalent to Algorithm 2, and requires four iterations to determine a solution for the 3×4 problem. In practice, this results in $O(mn)$ complexity. The performance improvement over the baseline (NW+MODI) is estimated to be approximately five times after adjusting for asymptotic growth ($k \sim \text{five}$) with $m = n = 20$, which corresponds to a reduction of 65% reported for the (3,4) problem.

9. LIMITATIONS AND SCOPE FOR FUTURE WORK

Several constraints bound the present study. The adaptive selection rule was designed for and tested on TFNs only; its applicability to trapezoidal, Gaussian, or type-2 fuzzy numbers is not established and would require re-derivation of the operator-selection thresholds. The rule's two threshold parameters ($RS = 0.20$, $AI \in [0.40, 0.60]$) were set based on the theoretical analysis in the Appendix and have not yet been calibrated empirically on a large-scale benchmark library. The validation set of ten instances, while sufficient for a paired t-test to reach significance, is modest by the standards of computational experiments

in operations research, where hundreds of instances are typical. Scaling experiments beyond 3×4 problems would strengthen the generalization claim. Future research directions include: extension of the adaptive mechanism to trapezoidal and interval type-2 fuzzy numbers; development of a self-tuning variant that learns the threshold parameters from problem data; integration with metaheuristic frameworks (e.g., particle swarm, differential evolution) for large-scale multi-period FTPs; and application to real logistics datasets from manufacturing or e-commerce distribution. extending Module IV to handle unbalanced and fuzzy inputs directly.

10. CONCLUSION

This paper has introduced and validated a four -module hybrid framework for solving fuzzy transportation problems. The first module departs from the conventional practice of applying a single, fixed defuzzification operator to all TFNs: it instead evaluates each TFN's relative spread and asymmetry index individually and assigns the operator — centroid, arithmetic mean, geometric mean, or harmonic mean — that minimizes the expected conversion error for that specific TFN. The second module translates the resulting accuracy advantage into a tighter IBFS by feeding the improved crisp cost estimates into an enhanced VAM whose tie-breaking rule is cost-sensitive. The third module

applies MODI to certify optimality, drawing on a starting solution that is already close enough to optimal that, in most cases, no pivot is required.

On the fully worked 3×4 example the framework recovered the global optimum ($Z^* = 166$ units) after a single MODI iteration, compared to five iterations for the NW corner baseline. Across ten randomized instances the method returned a zero optimality gap on every trial, a 57% reduction in defuzzification error relative to the centroid method, and a 65% saving in computation time. All pairwise comparisons were statistically significant at $p < 0.05$.

The practical implication is straightforward: logistics planners who face uncertain costs, supplies, or demands can apply the proposed framework in any spreadsheet environment using the pseudocode of Section 4, and can trust the resulting allocation plan to be genuinely optimal rather than merely approximately so. Extending the framework to richer uncertainty representations and larger network scales remains an open and productive direction for future work.

The complexity of Module IV for the penalty method is at most $O(mn(m+n))$, which is equivalent to Algorithm 2, and requires four iterations to determine a solution for the 3×4 problem. In practice, this results in $O(mn)$ complexity. The performance improvement over the baseline (NW+MODI) is estimated to be approximately five times after adjusting for asymptotic growth ($k \sim \text{five}$) with $m = n = 20$, which corresponds to a reduction of 65% reported for the $(3,4)$ problem.

The proposed hybrid methodology displayed a zero-optimality gap for all ten randomized assessments and produced a 57% reduction in defuzzification error and a 65% reduction in computation time relative to the centroid method used in the complete fuzzy framework. All ten pairwise comparisons at the $\alpha < 0.05$ level were statistically significant. Logistics planners can apply this method using the pseudocode from Section 4 to create optimal allocations instead of only approximations in situations where costs, supply patterns and/or demand are uncertain.

Reference

1. Ahuja, R. K., Magnanti, T. L., & Orlin, J. B. (1993). *Network flows: Theory, algorithms, and applications*. Prentice-Hall.
2. Ali, I., & Ahmad, N. (2021). A review of fuzzy transportation problem solution approaches. *Journal of Intelligent and Fuzzy Systems*, 40(1), 1–18.
3. Ali, I., & Ahmad, N. (2024). Operator-sensitive defuzzification in logistics optimization. *Expert Systems with Applications*, 210, 118437.
4. Aneja, Y. P., & Nair, K. P. K. (1979). Bicriteria transportation problem. *Management Science*, 25(1), 73–78.
5. Balinski, M. L. (1986). A competitive (dual) simplex method for the assignment problem. *Mathematical Programming*, 34, 125–141.
6. Bellman, R. E., & Zadeh, L. A. (1970). Decision-making in a fuzzy environment. *Management Science*, 17(4), B-141–B-164.
7. Chanas, S., & Kuchta, D. (1996). A concept of the optimal solution of the transportation problem with fuzzy cost coefficients. *Fuzzy Sets and Systems*, 82(3), 299–305.
8. Charnes, A., & Cooper, W. W. (1954). The stepping stone method of explaining linear programming calculations in transportation problems. *Management Science*, 1(1), 49–69.
9. Chauhan, S. S., & Joshi, R. C. (2013). Solution of fuzzy transportation problem using improved VAM with robust ranking. *International Journal of Computer Applications*, 82(15), 6–12.
10. Dantzig, G. B. (1963). *Linear programming and extensions*. Princeton University Press.
11. Dubois, D., & Prade, H. (1980). *Fuzzy sets and systems: Theory and applications*. Academic Press.
12. Ebrahimnejad, A. (2014). A simplified new approach for solving fuzzy transportation problems with generalized trapezoidal fuzzy numbers. *Applied Soft Computing*, 19, 171–176.
13. Gani, A. N., & Assarudeen, S. N. M. (2012). A new operation on triangular fuzzy number for solving fuzzy linear programming problem. *Applied Mathematical Sciences*, 6(11), 525–532.
14. Ghosh, S., Roy, S. K., & Verdegay, J. L. (2021). Multi-objective fully intuitionistic fuzzy fixed-charge solid transportation problem. *Complex and Intelligent Systems*, 7(2), 1009–1023.
15. Goyal, S. K. (1984). Improving VAM for unbalanced transportation problems. *Journal of the Operational Research Society*, 35(5), 475–476.
16. Gupta, A., Kumar, A., & Kaur, A. (2012). A new method for solving linear multi-objective transportation problems with fuzzy parameters. *Applied Mathematics and Information Sciences*, 6(1), 131–140.
17. Hitchcock, F. L. (1941). The distribution of a product from several sources to numerous localities. *Journal of Mathematics and Physics*, 20(1–4), 224–230.
18. Kané, L., Diabaté, L., Diakité, D., Kané, S., & Bado, H. (2022). Comparative study of defuzzification methods for fuzzy transportation problems. *Mathematics and Statistics*, 10(3), 631–639.
19. Kaur, A., & Kumar, A. (2012). A new approach for solving fuzzy transportation problems using generalized trapezoidal fuzzy numbers. *Applied Soft Computing*, 12(3), 1201–1213.

20. Kaufmann, A., & Gupta, M. M. (1985). Introduction to fuzzy arithmetic: Theory and applications. Van Nostrand Reinhold.
21. Koopmans, T. C. (1949). Optimum utilization of the transportation system. *Econometrica*, 17, 136–146.
22. Kumar, A., & Subramanian, P. (2018). Triangular fuzzy numbers in transportation: Systematic review and applications. *Fuzzy Information and Engineering*, 10(4), 403–425.
23. Liu, S., Papageorgiou, L. G., & Shah, N. (2022). Multi-period fuzzy supply chain planning under demand uncertainty. *European Journal of Operational Research*, 296(2), 442–459.
24. Mendel, J. M. (2001). Uncertain rule-based fuzzy logic systems: Introduction and new directions. Prentice-Hall.
25. Najafi, H. S., & Edalatpanah, S. A. (2013). A note on 'A new method for solving fully fuzzy linear programming problems.' *Applied Mathematical Modelling*, 37(14–15), 7865–7867.
26. Pandian, P., & Natarajan, G. (2010). A new algorithm for finding a fuzzy optimal solution for fuzzy transportation problems. *Applied Mathematical Sciences*, 4(2), 79–90.
27. Purushothkumar, M. K., Ananthanarayanan, M., & Dhanasekar, S. (2018). Fuzzy zero suffix method for fully fuzzy transportation problems. *International Journal of Pure and Applied Mathematics*, 119(9), 79–88.
28. Saravanan, G., Ramesh, G., & Kumar, N. (2025). Geometric and harmonic mean defuzzification in logistics optimization. *Soft Computing*, 29(1), 215–230.
29. Singh, S., & Yadav, D. (2021). A modified VAM for fully fuzzy transportation problems. *Fuzzy Sets and Systems*, 418, 107–127.
30. Srinivasan, R. (2021). Properties and operations of triangular fuzzy numbers in decision making. *Journal of Fuzzy Mathematics*, 29(2), 401–418.
31. Srinivasan, R., & Ganesan, K. (2013). Solving fuzzy transportation problems with triangular membership functions. *International Journal of Engineering Research and Applications*, 3(3), 1095–1098.
32. Yager, R. R., & Filev, D. P. (1994). Essentials of fuzzy modeling and control. Wiley.
33. Zadeh, L. A. (1965). Fuzzy sets. *Information and Control*, 8(3), 338–353.
34. Zhou, X., Wang, Y., Chai, J., Wang, L., Wang, S., & Lev, B. (2020). Sustainable supply chain evaluation with interval type-2 fuzzy data. *Information Sciences*, 504, 394–421.
35. Zimmermann, H. J. (1978). Fuzzy programming and linear programming with several objective functions. *Fuzzy Sets and Systems*, 1(1), 45–55.
36. Zimmermann, H. J. (2001). Fuzzy set theory and its applications (4th ed.). Springer.