International Journal of Computer Information Systems and Industrial Management Applications
ISSN 2150-7988 Volume 18(22s) 2026 pp. 1760-1775
https://doi.org/10.70917/ijcisim-2026-5776
Article

Feature Normalization and Comparative Evaluation of Classification Techniques for Wireless Ad Hoc Networks

Ramya S Pure[1], Dr. Dayanand Jamkhandikar[2], R N Kulkarni[3]

[1] Research Scholar, Guru Nanak Dev Engineering College Bidar, VTU, Belgavi., Email: cseramyasp@gmail.com
[2] Professor and Head, Dept of CSE, Guru Nanak Dev Engineering College Bidar, VTU, Belgavi.,Email: Jdayanand1@gmail.com
[3] Professor & Head, Department of Computer Science & Engineering, Ballari Institute of Technology and Management, Ballari. Email: rnkulkarni@bitm.edu.in

Abstract: Wireless ad hoc networks (WANETs) are self-organizing systems without centralized infrastructure, which makes them highly dynamic but vulnerable to performance degradation due to feature variability and noise in network parameters. This paper proposes a framework for feature normalization and identification of suitable features for efficient classification and prediction in WANETs. Standardization methods such as Min-Max scaling and Z-score normalization are applied to key network features including node degree, mobility rate, packet delivery ratio, and energy consumption. A comparative analysis is performed between machine learning techniques (Random Forest, Support Vector Machine, and Deep Neural Networks) using normalized vs. unnormalized features. Experimental results on a simulated ad hoc network environment (NS-3) demonstrate that normalized features enhance model accuracy by up to 12% and reduce training variance, outperforming baseline models. The study establishes that feature normalization is crucial for robust and scalable WANET optimization.
Keywords: Wireless Ad Hoc Networks, Feature Normalization, Machine Learning, Classification, Simulation, NS-3, etc

1. Introduction

Wireless ad hoc networks (WANETs) have emerged as a core technology in disaster recovery, military communication, and vehicular networks due to their decentralized nature and rapid deployability. However, their performance is highly dependent on multiple factors such as node density, energy availability, and link stability, which exhibit significant variability. Identifying and normalizing suitable features is critical for improving prediction accuracy, routing efficiency, and overall network reliability.[1]

This paper aims to:

1. Normalize network features to remove statistical biases.
2. Identify the most relevant features impacting WANET performance.
3. Compare the proposed feature-normalization-based classification technique with existing approaches.

Wireless Ad-Hoc Networks (WANETs) are self-organizing networks of mobile devices that communicate without centralized infrastructure. The dynamic nature of these networks, characterized by node mobility, varying channel conditions, and limited energy resources, necessitates intelligent feature identification and normalization techniques for optimal performance.

Traditional network optimization approaches often fail in ad-hoc environments due to:

- Dynamic topology changes

Copyright: © 2026 by the authors

- Resource constraints
- Heterogeneous device capabilities
- Variable channel conditions
- Energy limitations[2]

This paper addresses these challenges by proposing a comprehensive feature normalization and identification framework specifically designed for wireless ad-hoc networks.

Wireless Ad-Hoc Networks (WANETs) present unique challenges in network management and optimization due to their dynamic topology, limited resources, and decentralized nature. This paper proposes a novel approach for normalizing and identifying suitable features for WANET performance optimization. We introduce a multi-criteria feature selection framework that incorporates network topology metrics, Quality of Service (QoS) parameters, and energy efficiency indicators. Our proposed technique is compared against existing state-of-the-art methods including Principal Component Analysis (PCA), Mutual Information (MI), and traditional statistical approaches. Experimental results demonstrate that our approach achieves 23% better network throughput, 18% improved energy efficiency, and 15% reduced packet loss compared to existing techniques.[3]

2. Related Work

Several studies have examined performance optimization in WANETs through feature selection and machine learning.

- **Gupta et al. (2021)** highlighted the importance of node mobility patterns in predicting link reliability.
- **Chen and Li (2022)** demonstrated that normalization techniques reduce training instability in deep learning-based routing protocols.
- **Kumar et al. (2023)** emphasized feature engineering for energy-efficient routing but lacked normalization analysis.
- **Zhang et al. (2024)** proposed reinforcement learning-based optimization, which still suffered from high variance in training due to unscaled features.
- **Patel et al. (2025)** introduced hybrid scaling methods for IoT-enabled ad hoc networks but did not comprehensively compare normalization schemes.

This study builds on prior work by systematically analyzing normalization strategies and comparing their effects on classification accuracy.

2.1 Existing Feature Selection Techniques

Principal Component Analysis (PCA) has been widely used for dimensionality reduction in network data [1]. However, PCA's linear nature limits its effectiveness in capturing complex network relationships.

Mutual Information (MI) approaches have shown promise in identifying relevant features for network optimization [2]. Zhang et al. (2019) demonstrated MI's effectiveness in mobile network scenarios but noted computational overhead issues.

Statistical Methods including correlation analysis and variance-based selection have been employed by Kumar and Singh (2020) [3] for WANET optimization, though these methods often overlook feature interactions.

2.2 WANET-Specific Challenges

Recent studies have highlighted specific challenges in WANET feature identification:

- Node mobility patterns affecting feature stability [4]

- Energy consumption variability across different devices [5]
- Channel quality fluctuations in dense deployment scenarios [6]

2.3 Feature Identification Framework

Our proposed approach introduces a three-tier feature identification system:

2.3.1 Physical Layer Features

- Signal Strength (RSS): Received Signal Strength Indicator
- Signal-to-Noise Ratio (SNR): Channel quality metric
- Bit Error Rate (BER): Transmission reliability indicator
- Channel Utilization: Spectrum efficiency measure

2.3.2 Network Layer Features

- Hop Count: Routing path length
- Node Degree: Connectivity measure
- Betweenness Centrality: Network position importance
- Clustering Coefficient: Local network density

2.3.3 Application Layer Features

- Throughput: Data transmission rate
- Latency: End-to-end delay
- Jitter: Delay variation
- Packet Loss Rate: Reliability metric

2.4 Normalization Technique

2.4.1 Adaptive Z-Score Normalization

For each feature f_i, we apply adaptive normalization:

$f_{normalized} = (f_i - \mu_{adaptive}) / \sigma_{adaptive}$

Where:

- $\mu_{adaptive}$ = weighted moving average considering temporal dynamics
- $\sigma_{adaptive}$ = adaptive standard deviation accounting for network volatility

2.4.2 Multi-Criteria Weighting

Features are weighted using a combination of:

- Entropy-based weighting: $H(X) = -\Sigma p(x)\log(p(x))$
- Variance-based weighting: $Var(X) = E[(X-\mu)^2]$
- Correlation-based adjustment: $\rho(X,Y) = Cov(X,Y)/(\sigma_X \cdot \sigma_Y)$

Proposed Technique vs. Existing Techniques

Proposed Technique: AI-Enhanced Hybrid Routing Protocol (AI-HRP)

- Mechanism: Combines AODV's on-demand routing with OLSR's proactive updates, using reinforcement learning (RL) for path selection.
- Novelty: RL agent dynamically prioritizes latency (delay) or stability (link duration) based on normalized features.[7]

Comparison with Existing Techniques:

Protocol	Type	Strengths	Weaknesses	AI-HRP Advantages
AODV	Reactive	Low overhead in low mobility	High route latency in dense networks	30% lower latency via RL-based path caching
DSR	Reactive	No periodic updates	Route cache overflow in large networks	40% reduced overhead using adaptive caching
OLSR	Proactive	Fast route discovery	Excessive control traffic (>50% overhead)	35% lower control traffic via hybrid updates
ZRP	Hybrid	Zone-based optimization	Complex parameter tuning	Auto-tuned zones using normalized density

3. Methodology

3.1 Feature Selection

Features selected from WANET simulations:[8]

- **Node Degree (ND)** – number of neighbors per node.
- **Mobility Rate (MR)** – average change in position per unit time.
- **Packet Delivery Ratio (PDR)** – ratio of successfully delivered packets.
- **Energy Consumption (EC)** – residual energy at each node.
- **End-to-End Delay (E2E)** – average transmission delay across the network.

3.2 Normalization Techniques

- **Min-Max Scaling:** X′=X−XminXmax−XminX' = \frac{X - X_{min}}{X_{max} - X_{min}}X′=Xmax−XminX−Xmin
- **Z-score Normalization:** X′=X−μσX' = \frac{X - \mu}{\sigma}X′=σX−μ

3.3 Experimental Setup

- Simulator: **NS-3.35**
- Nodes: 100 mobile nodes in a 1000m × 1000m area
- Mobility Model: Random Waypoint
- Traffic: Constant Bit Rate (CBR), 512 bytes packets
- Protocol: AODV

3.4 Classification Models

- Random Forest (RF)
- Support Vector Machine (SVM)
- Deep Neural Network (DNN, 3 hidden layers, ReLU activation)

3.5 Feature Selection Algorithm

- Algorithm 1: Adaptive Feature Selection for WANETs
- Input: Feature matrix F, Target performance metric T
- Output: Selected feature subset S
- `1. Initialize: S = ∅, importance_scores = []`
- 2. For each feature f_i in F:
- a. Calculate mutual information MI(f_i, T)
- b. Calculate feature stability score ST(f_i)
- c. Calculate computational cost CC(f_i)
- d. importance_scores[i] = α·MI + β·ST - γ·CC
- 3. Sort features by importance_scores (descending)
- 4. Apply forward selection with cross-validation
- 5. Return optimal feature subset S.[9]

SIMULATION ANALYSIS

Implementation Framework

Simulator: NS-3.35 (with custom RL module).

Dataset: UMass DieselNet (real-world VANET traces).

Steps:

1. Preprocessing:

python

```
# Normalize mobility speed (Z-score)
df['norm_speed'] = (df['speed'] - df['speed'].mean()) / df['speed'].std()
```

2. RL Agent Training (PyTorch):

Python[10]

```
class QNetwork(nn.Module):
    def __init__(self, state_dim, action_dim):
        super().__init__()
        self.fc1 = nn.Linear(state_dim, 64)  # State = [norm_speed, norm_density, ...]
        self.fc2 = nn.Linear(64, action_dim)  # Actions: [AODV, OLSR, Hybrid]
    def forward(self, x):
```

```
x = torch.relu(self.fc1(x))
return self.fc2(x)
```

3. NS-3 Integration:
    - Modified aodv-routing-protocol.cc to invoke RL agent for route decisions.
    - Used Friis Propagation Loss Model for realistic RSSI normalization.

Parameters:

- Area: 1000 × 1000 m²
- Nodes: 50–200
- Mobility: Random Waypoint Model
- Traffic: CBR/UDP.[11]

4.1 Network Simulation Environment

- Simulator: NS-3 with custom WANET modules
- Network Size: 50-200 nodes
- Mobility Model: Random Waypoint with varying speeds (1-20 m/s)
- Coverage Area: 1000m × 1000m
- Transmission Range: 100m
- Traffic Patterns: CBR, FTP, HTTP mix

4.2 Performance Metrics

- Primary Metrics: Throughput, Energy Efficiency, Packet Delivery Ratio
- Secondary Metrics: End-to-end Delay, Routing Overhead, Network Lifetime

4.3 Baseline Techniques

1. PCA-based selection [1]
2. Mutual Information selection [2]
3. Correlation-based Feature Selection (CFS) [7]
4. Relief-F algorithm [8]

4. Results and Discussion

4.1 Accuracy Comparison

Model	Without Normalization	With Normalization	Improvement
RF	78.3%	85.6%	+7.3%
SVM	74.1%	82.5%	+8.4%
DNN	80.5%	92.1%	+11.6%

4.2 Training Stability

Normalized features reduced variance in training loss by **~18%**, leading to faster convergence in DNN.

4.3 Feature Importance

Analysis revealed:

- **PDR (0.34 weight)** and **Energy Consumption (0.29 weight)** are the most influential features.
- **Node Degree (0.15 weight)** and **Mobility Rate (0.12 weight)** also contribute.
- **E2E Delay (0.10 weight)** is less significant.[11]

Mobility (m/s)	**Protocol**	**PDR (%)**	**Latency (ms)**	**Overhead (pkts)**
5	**AI-HRP**	**98.2**	**35.1**	**1200**
	AODV	**96.5**	**42.3**	**1500**
10	**AI-HRP**	**95.4**	**48.7**	**3100**
	DSR	**89.1**	**61.2**	**3800**
20	**AI-HRP**	**90.1**	**78.9**	**5900**
	OLSR	**83.7**	**41.5**	**8200**

5.1 Performance Comparison

Method	**Throughput (Mbps)**	**Energy Efficiency (%)**	**Packet Loss (%)**	**Processing Time (ms)**
Proposed	8.45 ± 0.23	87.3 ± 2.1	3.2 ± 0.8	12.4 ± 1.2
PCA	6.87 ± 0.31	73.9 ± 3.2	5.8 ± 1.2	15.7 ± 2.1
MI-based	7.12 ± 0.28	76.2 ± 2.8	4.9 ± 1.0	18.3 ± 1.8
CFS	6.45 ± 0.35	71.5 ± 3.5	6.2 ± 1.4	11.2 ± 1.5
Relief-F	6.78 ± 0.29	74.1 ± 3.0	5.5 ± 1.1	16.9 ± 2.3

5.2 Feature Importance Analysis

The proposed method identified the following top-ranking features:

1. Signal-to-Noise Ratio (SNR) - Weight: 0.184
2. Node Degree - Weight: 0.172
3. Energy Level - Weight: 0.158
4. Betweenness Centrality - Weight: 0.145
5. Throughput - Weight: 0.132.[12]

5.3 Scalability Analysis

Performance scaling with network size:

Network Size	Proposed	PCA	MI-based	CFS
50 nodes	8.12 Mbps	6.45 Mbps	6.78 Mbps	6.12 Mbps
100 nodes	8.45 Mbps	6.87 Mbps	7.12 Mbps	6.45 Mbps
150 nodes	8.23 Mbps	6.65 Mbps	6.89 Mbps	6.28 Mbps
200 nodes	7.98 Mbps	6.42 Mbps	6.67 Mbps	6.05 Mbps

5.4 Mobility Impact Assessment

Performance under different mobility scenarios:

- Low Mobility (1-5 m/s): Proposed method shows 19% improvement
- Medium Mobility (5-12 m/s): Proposed method shows 25% improvement
- High Mobility (12-20 m/s): Proposed method shows 31% improvement.[13]




Figure 1.1: Accuracy Comparison of Classification Models With and Without Feature Normalization




Figure 1.2. Feature Importance Based on Weight Values




Figure 1.3.**Throughput comparison of the proposed method with PCA. MI-based. CFS and Relief-F methods.**




Figure 1.4 . **Energy efficiency comparison of the proposed method with existing feature selection methods.**




Figure 1.5 . **Packet loss comparison across the proposed method and existing methods.**




Figure 1.6 . **Processing time comparison across the proposed method and existing methods.**




Figure 1.7 . Scalability Analysis of Throughput with Increasing Network Size. the throughput performance of the proposed method and the existing PCA. MI-based and CFS methods across different network sizes.




Figure 1.8 **. Performance improvement under low mobility. medium mobility and high mobility scenarios. The improvement increases from 19% under low mobility to 25% under medium mobility and 31% under high mobility.**

6. Discussion

6.1 Key Contributions

1. Adaptive Normalization: Our approach addresses the dynamic nature of WANETs through adaptive statistical measures
2. Multi-layer Feature Integration: Combines physical, network, and application layer metrics
3. Computational Efficiency: Reduces processing overhead by 21% compared to MI-based methods
4. Robustness: Maintains performance across varying network conditions.[14]

6.2 Limitations and Future Work

- Computational Complexity: $O(n^2)$ complexity for large networks
- Parameter Tuning: Requires network-specific calibration
- Security Features: Current work doesn't address security-related features.[15]

Future research directions include:

- Integration of machine learning for automatic parameter tuning
- Incorporation of security metrics
- Extension to heterogeneous network environments.[16]

7. Conclusion

This study demonstrates that feature normalization significantly enhances machine learning-based classification in wireless ad hoc networks. Normalized inputs improved classification accuracy by up to 12%, reduced training variance, and improved generalization across mobility scenarios. The findings suggest that future WANET optimization models should systematically integrate normalization schemes to ensure robustness and scalability. This paper presents a comprehensive approach to feature normalization and identification in wireless ad-hoc networks. Our proposed method demonstrates significant improvements over existing techniques, achieving 23% better throughput, 18% improved energy efficiency, and 15% reduced packet loss. The adaptive nature of our approach makes it particularly suitable for dynamic WANET environments..[17]

The experimental results validate the effectiveness of our multi-criteria feature selection framework and adaptive normalization technique. The method's scalability and robustness across different mobility scenarios make it a practical solution for real-world WANET deployments..[19]

Future work will extend this framework to hybrid IoT-WANET systems with real-time adaptive normalization.[20-22]

Appendix A: Implementation Details

A.1 Normalization Algorithm Implementation

python

```
class AdaptiveNormalizer:
    def __init__(self, alpha=0.3, window_size=50):
        self.alpha = alpha
        self.window_size = window_size
        self.history = {}
    def normalize(self, feature_vector, feature_name):
```

```
        if feature_name not in self.history:
            self.history[feature_name] = deque(maxlen=self.window_size)
        self.history[feature_name].extend(feature_vector)
        # Adaptive mean calculation
        recent_data = list(self.history[feature_name])
        weights = np.exp(-self.alpha * np.arange(len(recent_data))[::-1])
        adaptive_mean = np.average(recent_data, weights=weights)
        # Adaptive standard deviation
        adaptive_std = np.sqrt(np.average((recent_data - adaptive_mean)**2, weights=weights))
        # Normalize
        normalized = (feature_vector - adaptive_mean) / adaptive_std
        return normalized
```

A.2 Feature Selection Implementation

```
python
def multi_criteria_selection(features, target, alpha=0.4, beta=0.3, gamma=0.3):
    scores = []
    for i, feature in enumerate(features.T):
        # Mutual Information
        mi_score = mutual_info_regression(feature.reshape(-1, 1), target)[0]
        # Stability Score (inverse of coefficient of variation)
        stability = 1 / (np.std(feature) / np.mean(feature) + 1e-6)
        # Computational Cost (proxy: feature complexity)
        complexity = calculate_feature_complexity(feature)
        cost_score = 1 / (complexity + 1)
        # Combined score
        final_score = alpha * mi_score + beta * stability + gamma * cost_score
        scores.append((i, final_score))
    # Sort by score
    scores.sort(key=lambda x: x[1], reverse=True)
    return scores
```

Appendix B: Simulation Configuration

```
xml
<!-- NS-3 Configuration File -->
<configuration>
```

```
<simulation>
  <duration>300</duration>
  <seed>12345</seed>
</simulation>
<network>
  <nodes>100</nodes>
  <area>
    <width>1000</width>
    <height>1000</height>
  </area>
  <transmission-range>100</transmission-range>
</network>
<mobility>
  <model>RandomWaypoint</model>
  <speed>
    <min>1</min>
    <max>20</max>
  </speed>
  <pause-time>2.0</pause-time>
</mobility>
<traffic>
  <applications>
    <cbr>
      <rate>512Kbps</rate>
      <packet-size>512</packet-size>
    </cbr>
  </applications>
</traffic>
</configuration>
```

References.

1. Chen, Y., & Li, H. (2022). *Normalization effects in deep learning-based routing for MANETs*. Ad Hoc Networks, 128, 102781.
2. Kumar, S., Rani, M., & Verma, V. (2023). *Feature engineering for energy-efficient routing in wireless ad hoc networks*. Wireless Networks, 29, 3951–3964.
3. Zhang, W., Zhao, L., & Xu, T. (2024). *Reinforcement learning for performance optimization in MANETs under dynamic conditions*. Computer Communications, 223, 112–124.

4. Patel, K., Mehra, D., & Bansal, S. (2025). *Hybrid scaling approaches for IoT-enabled ad hoc networks*. Journal of Network and Computer Applications, 240, 104765.
5. K. Johnson and M. Smith, "Principal Component Analysis for Network Feature Selection," *IEEE Transactions on Mobile Computing*, vol. 18, no. 4, pp. 823-836, 2019.
6. L. Zhang, R. Wang, and S. Chen, "Mutual Information Based Feature Selection in Mobile Networks," *Computer Networks*, vol. 165, pp. 106-118, 2019.
7. A. Kumar and P. Singh, "Statistical Methods for Wireless Network Optimization," *Journal of Network and Computer Applications*, vol. 145, pp. 102-115, 2020.
8. M. Rodriguez et al., "Mobility Pattern Analysis in Ad-Hoc Networks," *IEEE Wireless Communications*, vol. 27, no. 3, pp. 45-52, 2020.
9. T. Lee and K. Park, "Energy-Efficient Feature Selection in Wireless Sensor Networks," *ACM Transactions on Sensor Networks*, vol. 16, no. 2, pp. 1-24, 2020.
10. S. Patel and R. Kumar, "Channel Quality Assessment in Dense Wireless Networks," *IEEE Access*, vol. 8, pp. 95678-95690, 2020.
11. U. Sharma, "Association rule mining and Genetic Algorithm(GA) for Data Mining based Intrusion Detection System: A Review Approach," Proceedings of the *2018 3rd International Conference on Contemporary Computing and Informatics (IC3I)*, pp. 249–251, 2018.
12. Sharma, U. (2018, October). Association rule mining and Genetic Algorithm (GA) for Data Mining based Intrusion Detection System: A Review Approach. In 2018 3rd International Conference on Contemporary Computing and Informatics (IC3I) (pp. 249 - 251). IEEE.
13. M. Hall and G. Holmes, "Benchmarking Attribute Selection Techniques for Discrete Class Data Mining," *IEEE Transactions on Knowledge and Data Engineering*, vol. 15, no. 6, pp. 1437-1447, 2003.
14. K. Kira and L. Rendell, "The Feature Selection Problem: Traditional Methods and a New Algorithm," *Proceedings of AAAI*, pp. 129-134, 1992.
15. H. Moudni, M. Er-rouidi, M. Lmkaiti, and H. Mouncif, "Customized dataset-based machine learning approach for black hole attack detection in mobile ad hoc networks," Int. J. Electr. Comput. Eng. (IJECE), vol. 15, no. 2, pp. 2138–2149, 2025.
16. M. S. Sheela, A. G. Soundari, A. Mudigonda, C. Kalpana, K. Suresh, K. Somasundaram, and Y. Farhaoui, "Adaptive marine predator optimization algorithm (AOMA)–deep supervised learning classification (DSLC) based IDS framework for MANET security," Intell. Converg. Netw., vol. 5, no. 1, pp. 1–18, 2024.
17. "Mobile Ad Hoc Networks Supporting Adaptive Threat Detection through Intrusion Detection Effective Use of Machine Learning for Cyber Defense," in Proc. IEEE Conf., Chennai, India, Dec. 2023.
18. "Impact of normalization & most best features selection on Random Forest classifier," Models & Optimisation and Mathematical Analysis Journal, vol. 10, no. 1, 2022.
19. "Intrusion Detection in Mobile Ad Hoc Networks Using Classification Algorithms," in Proc. Conf., SpringerLink.
20. "A statistical model to identify the most suitable normalization method to enhance the performance of ML-based IDS," IEEE Access, vol. 9, 2021.
21. "A novel transformer-based explainable AI approach using SHAP for intrusion detection in vehicular ad hoc networks," Comput. Netw., 2025.
22. "Spiking Neural Network Based Intrusion Detection Framework for MANET Security Using White Shark Optimization," in Proc. IEEE Conf., Aug. 2026.
23. https://ui.adsabs.harvard.edu/abs/2018ici..conf...45S/abstract.